

ICU HB 450 C
copyright
ACADEMY

















ICU HB 450 C FOUR FUNCTION MOTORIZED INTENSIVE CARE HOSPITAL BED

- SUITABLE FOR CONSTRUCTION COATING FUNCTION & POWER**

Intensive Care Units, Clinics, Long term cares, Nursing, Home care, Academic studies.
Made of steel construction. Gas metal arc welding technique provides strength and durability.
All metal constructions are painted with the high quality epoxy powder paint at 180°C.
ICU HB 450 C , backrest and foot part movements are made by 6000 N/m³ electric actuators. Height and trendelenburg movements are made by column type two actuators. Equipped with electronic CPR function.
- SAFETY PLATFORM**

PP plastic head and foot boards and side rails secure the patient. Plastic bumpers at each corner.
The bed platform is covered with anti-bacterial, special design ABS thermo-vacuum plastic coating.
Optional back part is X-RAY permeable HPL compact laminate so the bed can be used for radiological processes.
- MOBILITY EQUIPPED WITH**

ICU HB 450 C, equipped with 125 mm diameter wheels, central brake with directional locking system.
Back up battery, IV pole, Drainage bag holder, Corner bumpers, Universal brackets for lifting pole and orthopedic traction set.

HB 450 C ALL FUNCTIONS						
HEIGHT 45-80 CM	BACK REST ADJUST 0-70°	LEG REST ADJUST 0-35°	CHAIR	TRENDELBURG 14°	R.TRENDELBURG 14°	CARDIO CPR
						
ACTUATOR COLUMN TYPE	ACTUATOR 6000 N/m ³	ACTUATOR 6000 N/m ³	ACTUATOR 6000 N/m ³	ACTUATOR COLUMN TYPE	ACTUATOR COLUMN TYPE	ACTUATOR 6000 N/m ³
OPTIONS AND ACESORIES						
AUTO REGRESSION	✓ NURSE CONTROL	OPT PEDAL HI-LOW	OPT X RAY PLATFORM	OPT PNEUMATIC 5th WHEEL	OPT LIFTING POLE	OPT LENGTH EXTENSION
						
INFORMATIONS						
DIMENSIONS		INFO		STANDARDS		TRANSPORTATION
WIDTH / mm	1050	POWER	24 VDC 5A / 12 VDC 10A	ISO 13485	ISO 9001	PACKAGING
LENGTH / mm	2100	PROTECT	IP 66	ISO 45001	ISO 14001	Cartoon Box
HEIGHT / mm	450-800	WARRANTY	2 Years	ISO 10002	CE	40 FT CONTAINER
WEIGHT / Kg	100	MDR	Class I	UDI-DI No: 8683255452064AE		80 Pcs.