## LATURCA DESIGN





## ICU BB 450 CS FOUR FUNCTION MOTORIZED INTENSIVE CARE HOSPITAL BED

**SUITABLE FOR** Intensive Care Units, Clinics, Long term cares, Nursing, Home care, Academic studies.

**CONSTUCTION** Made of steel construction. Gas metal arc welding technique provides strength and durability. **COATING** All metal constructions are painted with the high quality epoxy powder paint at 180°C.

FUNCTION & ICU BB 450 CS , back rest and foot part movements are made by two 6000 N/m³ electric actuators. Height and trendelenburg movements are made by two column type actuators. Equipped with

electronic CPR function. Patient weight can be monitored instantly on the LCD screen.

SAFETY PP plastic head and foot boards and side rails secure the patient. Plastic bumpers at each corner.

PLATFORM The bed platform is covered with anti-bacterial, special design ABS thermo-vacuum plastic coating.

Optional back part is X-RAY permeable HPL compact laminate so the bed can be used for radiological

processes.

MOBILITY ICU BB 450 CS, equipped with 125 mm diameter wheels, central brake with directional locking system.

**EQUIPPED WITH** Back up battery, IV pole, Drainage bag holder, Corner bumpers, Universal brackets for lifting pole and orthopedic traction set.

ICU BB 450 CS ALL FUNCTIONS									
HEIGHT	HEIGHT BACKREST		CHAIR	TRENDELENBURG	R.TRENDELENBURG	CARDIO CPR			
45-80 CM	ADJUST 0-70°	ADJUST 0-35°		14°	14°				
ACTUATOR	<b>ACTUATOR</b>	ACTUATOR	<b>ACTUATOR</b>	<b>ACTUATOR</b>	<b>ACTUATOR</b>	<b>ACTUATOR</b>			
COLUMN TYPE	6000 N/m <sup>3</sup>	6000 N/m <sup>3</sup>	6000 N/m <sup>3</sup>	COLUMN TYPE	COLUMN TYPE	6000 N/m <sup>3</sup>			
OPTIONS AND ACCESORIES									
AUTO ✓	NURSE ✓	PEDAL OPT	X RAY ✓	SCALE ✓	LIFTING OPT	LENGTH OPT			
REGRESSION	CONTROL	HI-LOW	PLATFORM	ELECTROMAGNETIC	POLE	EXTENSION			
	2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			KG		<b></b>			
INFORMATIONS									

INFORMATIONS										
DIMENSIONS			INFO		TANDARDS	TRANSPORTATION				
WIDTH / mm	1050	POWER	24 VDC 5A / 12 VDC 10A	ISO 13485	ISO 9001	PACKAGING				
LENGTH / mm	2100	PROTECT	IP 66	ISO 45001	ISO 14001	Cartoon Box				
HEIGHT / mm	450-800	WARRANTY	2 Years	ISO 10002	CE	40 FT CONTAINER				
WEIGHT / Kg	154	MDR	Class I	UDI-DI No: 8	3683255452064AE	80 Pcs.				