



ST 02 VENTUS








ST 02 VENTUS TWO FUNCTION GENERAL PURPOSE STRETCHER








- SUITABLE FOR CONSTRUCTION COATING FUNCTION & POWER SAFETY PLATFORM MOBILITY EQUIPPED WITH

Clinics, Emergency units, First AID units, Academic studies.
Made of steel construction. Gas metal arc welding technique provides strength and durability.
All metal constructions are painted with the high quality epoxy powder paint at 180°C.
ST 02 VENTUS,backrest movement is made by 500 N/m³ pneumatic gas spring. Trendelenburg movement is made by 500 N/m³ pneumatic gas spring. Also equipped with pneumatic CPR function.
Chrome plated foldable aluminium side rails secure the patient. Plastic bumpers at each corner.
The stretcher platform is covered with anti-bacterial, water proof leather, upholstered high density polyurethane foam, durability (laminated high gloss) coating decks.
ST 02 VENTUS has 125 mm diameter wheels with diagonal braking system.
IV pole, corner bumpers, universal brackets for lifting pole and drainage holder.


ST 02 VENTUS TWO FUNCTION GENERAL PURPOSE STRETCHER ALL FUNCTION

BACK REST 70°	TRENDELBURG 12°	POLYURETHANE MATTRESS	CARDIO CPR	FOLDABLE IV POLE		
						
GAS SPRING	GAS SPRING	P. FOAM	GAS SPRING	METAL		

OPTIONS AND ACCESSORIES

OXYGEN TUBE HOLDER	OPT X RAY HPL PLATFORM	OPT METAL SIDE RAILS	OPT BASKET METAL	OPT FOLDABLE PUSH BAR	OPT SAFETY BELTS	OPT LENGTH EXTENSION
						

INFORMATION

DIMENSIONS		INFO		STANDARDS		TRANSPORTATION
WIDTH / mm	700	POWER	PNEUMATIC	ISO 13485	ISO 9001	PACKAGING
LENGTH / mm	2050	PROTECT	IP 43	ISO 45001	ISO 14001	Cartoon Box
HEIGHT / mm	800	WARRANTY	2 Years	ISO 10002		40 FT CONTAINER
WEIGHT / Kg	58	MDR	Class I			92 Pcs.